

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. E - 6597 - 2
1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Hixon Development Company		7. Unit Agreement Name
3. Address of Operator P. O. Box 2810, Farmington, New Mexico		8. Farm or Lease Name Kelly State
4. Location of Well UNIT LETTER A , 790 FEET FROM THE North LINE AND 1120 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 25N RANGE 12W NMPM.		9. Well No. 1
		10. Field and Pool, or Wildcat Wildcat PC
15. Elevation (Show whether DF, RT, GR, etc.) 6229' GL		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>		COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well 3-25-77. Drilled 7 7/8" hole to 35'. Ran 1-joint 5 1/2" 14# 8 RD J-55 ST&C surface casing and set @ 33'. Cemented with 7 sacks Class B cement, 2% CaCl. Drilled 4 3/4" hole to a TD of 1330'. Set 2 7/8" 6.5# 8 RD J-55 EUE casing @ 1316'. Cemented with 50 sacks 50-50 Pozmix and 25 sacks Class A cement. All cement contained 2% CaCl. Cement top by temperature survey is 64' GL.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cedrick L. Kendrick Petroleum Engineer DATE April 11, 1977

Original Signed by P. Kendrick SUPERVISOR TITLE DATE

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: