

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Exploration Company

3. ADDRESS OF OPERATOR

P.O. Box 4289, Farmington, New Mexico 87499-4289

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1140' FNL, 1080' FEL, Section 25, T-25-N, R10-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, WT, GR, etc.)

6711 KB

5. LEASE DESIGNATION AND SERIAL NO.

NM 23064

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf Little Federal 25

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 25, T-25-N, R-10-W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 1) Circulate the hole with mud.
- 2) Spot a plug from PBTD (2598') to 1831' to cover the Pictured Cliffs perforations (1884 - 1894).
- 3) Spot a plug from 1510' to 1610' to cover the Fruitland.
- 4) Spot a plug from 1148' to 1248' to cover the Kirtland.
- 5) Spot a plug from 918' to 1018' to cover the Ojo Alamo (Primary cement should cover the outside of the casing from 900' to 2021').
- 6) Perforate the 4 1/2" casing at 350' and cement inside and outside to 250'.
- 7) Cover the casing and annular space from 100' to surface with cement and install a dryhole marker.
- 8) Remove equipment and restore surface.

18. I hereby certify that the foregoing is true and correct

SIGNED

William D. Welch

TITLE Production Engineer

DATE April 10, 1984

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

APR 10 1984  
D. MILLER  
ACTING AREA MANAGER

\*See Instructions on Reverse Side

NMOCC