

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-verse side)

Form approved.
Budget Bureau No. 42-11424.
5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-1423

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ka Da Pah

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

NPP - PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

3-25N-12W NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Hixon Development Company

3. ADDRESS OF OPERATOR

P. O. Box 2810, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

790' FSL, 1000' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6188' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Drilling Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well was spudded 8-13-77. Drilled 7 7/8" hole to 67'. Set 65' 5 1/2" 15.5# J-55 casing. Cemented with 15 sacks Class A cement, 2% CaCl. Drilled 4 3/4" hole to 1250'. Ran 2 7/8" 6.5# J-55 8RD EUE casing to 1242'. Cemented with 75 sacks Class G cement, 2% CaCl. Perforated Pictured Cliffs sand 1117'-33', 1112'-14' with 2-SPF. Acidized with 500 gallons mud acid. Fraced well with 20,000# sand 97,000 SCF nitrogen. Well shut in waiting on separator installation.

RECEIVED

SEP 21 1977

U. S. GEOLOGICAL SURVEY
FEDERAL BUREAU OF RESEARCH



18. I hereby certify that the foregoing is true and correct

SIGNED

Alvin H. Terrell

Petroleum Engineer

DATE

9/20/77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: