## UNITED STATES DEPARTMENT OF THE INTERIOR 15 77 1: 13 BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

	Sundry Notices and Repo	orts on vvens	•	
****			5.	Lease Number N <del>OO-C</del> -14-20-603-323
1. Typ	e of Well		6.	If Indian, All. or
	Gas			Tribe Name
				Navajo
			7.1	Unit Agreement Name
	ne of Operator	- Kill of Lang 1, 5 (SIR)		
Ce	entral Resources, Inc.		uNI	
2 Ado	Iress & Phone No. of Operator	Landa L	} <i>β</i> ?/Ω¢	Well Name & Number
	$\times$ 1247 Bloomfield NM87413 (505) 632-3476	000 9 37 3	9.	Gle Na Nup Pah #1
PO Bo	X 124/ BIOOMITEIG MM0/413 (303) 032-34/0	Digital of	9.	<b>API Well No</b> . 30-045-22709
Locatio	n of Well, Footage, Sec., T, R, M		10.	Field and Pool
			10.	WAW Fruitland PC
185	0' FSL and 790' FEL, Sec. 5, T-25-N, R-12-W,			VVAVV I Tuttiand I C
			11.	County & State
				San Juan County, NM
				·
	CK APPROPRIATE BOX TO INDICATE NATURE OF	NOTICE, REPORT, OTH	ER D	ATA
Тур	e of Submission Type of Action			
		Change of Plans		
		New Construction		
	X Subsequent Report Plugging Back	Non-Routine Fractur	ing	
	Casing Repair	Water Shut off	:	
	Final Abandonment Altering Casing Other -	Conversion to Inject	ion	
	Other -			
13.	Describe Proposed or Completed Operations	- 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10		· · · · · · · · · · · · · · · · · · ·
1 11 00	Pood rig and aguinment to location DLL Leveut reli	of line to mit. Cheek well m		50# 1
1-11-99 Road rig and equipment to location, RU. Layout relief line to pit. Check well pressure: casing tubing 20#, bleed well down. POH and LD 33 joints 1-1/4" tubing. Pump 10 bbls water down				re. casing ou# and
	Plug #1 with 28 sxs Class B cement pumped down 2	2-7/8" casing to fill Fruitland	d ned	forations displaced
	to 200'. Shut in well and WOC. RD rig and equipmer	nt, move off location.	u pen	orations, displaced
		.,		
1-12-99	Safety Meeting. Road cementing equipment to locati	ion. RU A-Plus wireline tru	ick ar	nd RIH, tag cement
at 324'. Perforate 2 bi-wire squeeze holes at 82'. Attempt to establish circulation to surface of bradenhead or outside the 5-1/2" surface casing with 10 bbls water, nothing to surface. J. Mor				to surface out the
				face. J. Morrison,
	BLM, approved procedure change to bullhead dow	n casing. Plug #2 with 2	24 sx	s Class B cement
	pumped down 2-7/8" casing from 82' to cover sque	eze holes and surface cas	sing s	hoe, final squeeze
	pressure 500# and no circulation to surface. Shut in v	well and WOC. RD cemen	t equi	pment and MOL.
1_13_00	Safety Meeting. Cut off wellhead and install P&A mark	or 10 eye Class B coment		
. 10 33	J. Morrison, BLM was on location 1/12/99.	er, 10 sas class b cement.		
	The state of the s			
14. I hei	eby certify that the foregoing is true and correct.			
	D1 3 1 1 1200 011	.1		
Signed_	Rodney Z. Scale 2-13-99 Title District	TManager	_	Date1/21/99
	ace for Federal or State Office use)	ACC	EPT	ED FOR RECORD
APPRO\	/ED BY Title ION OF APPROVAL, if any:	/ 140 W		Date
COMDIT	ION OF AFTINOVAL, II ally.		CC	B 2 2 1999
			1 L	U C C 1777

FARMINGTON FIELD OFFICE BY\_\_\_\_\_\_\_

FAT