

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

FORM NO. 100 (REV. 1-78)
INSTRUCTIONS ON REVERSE SIDE

Form Approved
Budget Bureau No. 42-11414

LEASE DESIGNATION AND SERIAL NO.

NM25444

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ON WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Hixon Development Company	8. FARM OR LEASE NAME Hixon Federal
3. ADDRESS OF OPERATOR P.O. Box 2810, Farmington, New Mexico 87401	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1850' FNL, 1500' FEL, Section 4, T25N, R12W	10. FIELD AND POOL, OR WILDCAT Farmington
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 4, T25N, R12W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6159' GLE
	12. COUNTY OR PARISH San Juan
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

The above captioned well appears to be an uncommercial recompletion prospect at the present time. It is proposed to backoff top joint of 2-7/8" casing and fill surface pipe with cement and erect a regulation dry hole marker (or remove casing to 4' below surface as specified).

It should be noted that this well's Pictured Cliffs sand interval perforations 1052'-1102' were squeezed and abandoned per our sundry dated 1/6/81

Plug must be set from 50' below surface casing shoe at 34' to surface (84' to surface)

RECEIVED

AUG 13 1982

U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature] Petroleum Engineer

DATE

8/12/82

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL

AUG 16 1982

TITLE

AS AMENDED

DATE

*See Instructions on Reverse Side

NMOCC

