

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM-25449

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Hixon Development Company

3. ADDRESS OF OPERATOR

P.O. Box 2810, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements \*  
See also space 17 below.)

At surface

860' FNL, 330' FWL, Section 22, T25N, R12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6268' GL

6280' KB

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hunter Wash

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 22-25N-12W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Progress

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Move in rotary tools. Spud well @ 5:00 pm 9-6-79. Drill 12-1/4" hole to 232'. Ran 213.73' 8-5/8" 24# J-55 ST&C casing with shoe and 2 centralizers to 226' KB. Dowell cemented casing with 200 sacks Class B 2% CaCl cement. Displaced with 14 BW. Good cement returns. WOC 12 hours. Flange up BOP. Pressure test casing to 800 psi for 30 minutes. Held OK. Drill out from under surface with 7-7/8" hole. Ran Totco surveys. Mud logger unit on well below surface. Depth 3070' in Menefee Sand. Weight on bit 40,000#, 75 RPM, mud pump with 5" liners, 64 SPM @ 1250 psi. Drilling with Gelex and water. BOP tested daily.

**RECEIVED**

SEP 11 1979

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct.

SIGNED

\_\_\_\_\_  
Petroleum Engineer

DATE 9-10-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*Y. MOC*

\*See Instructions on Reverse Side

