

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYForm Approved.  
Budget Bureau No. 42-R1424

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Amoco Production Company
3. ADDRESS OF OPERATOR  
501 Airport Drive Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 990' FNL & 1790' FWL Section 14  
AT TOP PROD. INTERVAL: same T25N, R14W  
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

## SUBSEQUENT REPORT OF:

(other) Spud & Set Casing

5. LEASE <u>N00-C-14-20-5503</u>
6. IF INDIAN, ALLOTTEE OR TRIBE NAME <u>Navajo Tribe</u>
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME <u>Navajo Tribal "AG"</u>
9. WELL NO. <u>1</u>
10. FIELD OR WILDCAT NAME <u>Wildcat</u>
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>NE/4, NW/4 Section 14, T25N, R14W</u>
12. COUNTY OR PARISH <u>San Juan</u>
13. STATE <u>New Mexico</u>
14. API NO. <u>30-045-23658</u>
15. ELEVATIONS (SHOW DF, KDB, AND WD) <u>6112' GL</u>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates; including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well on 9-27-79. Drilled to 253' and set 10-3/4", 32.75 pound surface casing at 249'. Cemented with 400 sx class "B" Neat cement containing 2% CaCl<sub>2</sub>.

Drilled 9-5/8" hole to 918' and set 8-5/8", 24.00 pound intermediate casing at 916'. Cemented with 150 sx class "B" Neat cement containing 50:50 Poz, 6% gel, 2 pound medium tuf plug 1 sx and 0.2% friction reducer. Tailed in with 35 sx class "B" Neat cement.

Presently drilling toward TD.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA

TITLE Dist. Adm. Supr. DATE 10-8-79

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

