5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NOO-C-14-20-5503 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	Navajo Tribe 7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas cother gas other	Navajo Tribal "AG" 9. WELL NO.
2. NAME OF OPERATOR	1 10. FIELD OR WILDCAT NAME
Amoco Production Company 3. ADDRESS OF OPERATOR Remainster NM 87/01	Wildcat 11. SEC., T., R., M., OR BLK. AND SURVEY OR
501 Airport Drive Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA NE/4 NW/4 Section 14, T25N, R14V
below.) AT SURFACE: 990' FNL x 1790' FWL Section 14, AT TOP PROD. INTERVAL: Same T25N, R14W	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 30-045-23658
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6112' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF U U FRACTURE TREAT U U U U U U U U U U U U U U U U U U U	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
ARANDON*	
(other) Change of depth in procedure	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Amoco Production Company's plug and abandon	nt to this work.)*
read as follows:	
(2) Spotted with 30 sx class "B" Neat cement	
This should be corrected to read as follows:	The state of the s
(2) Spotted with 30 sx class "B" N at cement	300' to 400'.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
TITLE Dist. Adm. S	Supr. DATE 11/6/79
SIGNED	
APPROVED BY TITLE	DATE
APPROVED BY THE CONDITIONS OF APPROVAL, IF ANY:	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
*See Instructions on Revers	se Side