

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Indian Bureau No. 1004-0135
Expires April 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NOO-C-14-20-5241

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dry Creek

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Bisti Lower Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 31, T25N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Coleman Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

Drawer 3337, Farmington, N.M. 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1970' FSL and 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6807 Gr

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Set bridge plug at 5175' and spot 25 sks cement on top
2. Roll hole with 9.2 # mud
3. Perforate Cliffhouse at 3080' and cement inside and outside 4 1/2" casing from 3080 to 2980 25 sks.
4. Chacra perf. 2385' set 25 sk plug, inside and outside of 4 1/2" casing 2385' to 2285'
5. Pictured Cliffs and Fruitland perf. 1665' set 25 sk plug inside and outside of 4 1/2" casing 1665 to 1520
6. Ojo Alamo perf. 860' set 40 sk plug inside and outside of 4 1/2" casing 860' to 680'
7. Surface perf. 261' set 25 sk plug inside and outside 4 1/2" casing 261' to 161'
8. Top plug 50' - 0 cement inside and out 4 1/2" casing 10 sks
9. Erect dry hole marker
10. Clean location and seed to specifications

RECEIVED

NOV 16 1987

FOR THE FOLLOWING IS TRUE AND CORRECT

W. M. Gallaway

W. M. Gallaway, Engineer

NOV 16 1987

TITLE

John Skelton

Who has been on the well site

NOV 16 1987