

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
GEORGE L. COLEMAN

3. ADDRESS OF OPERATOR **c/o W. S. Callaway
101-2 Petroleum Plaza Bldg., Farmington,**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **990' FWL and 2235' FWL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input checked="" type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NOO-C-14-20-5266

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Dry Creek

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Wisti Gallup

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 30, T25N, R11E

12. COUNTY OR PARISH
San Juan

13. STATE
N. M.

14. API NO.
W/A

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6804' GA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 10-8-79 ran 216' of 3 5/8" 28% surface casing cemented with 100 sacks, waited 8 hours, tested for 20 minutes to 1000#. Cement held.

On 10-10-79 ran 5339.79' of 4 1/2" 10.50% casing cemented with 110 sacks of cement. Bumped plug under 1500# of pressure, held for 10 min., released, float held.

Subsurface Safety Valve: Manu. and Type **Dowell- orifice fill collar** Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED **W. S. Callaway** TITLE **Operator** DATE

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY **McKuchera** TITLE **Operator** DATE

CONDITIONS OF APPROVAL, IF ANY:
MAR 11 1980

FARMINGTON DISTRICT
BY **McKuchera**



*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. Consult local

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.