

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		87 NOV -9 PM 12:15	
2. NAME OF OPERATOR Coleman Oil and Gas, Inc.		FARMINGTON RESOURCE AREA FARMINGTON, NEW MEXICO	
3. ADDRESS OF OPERATOR Drawer 3337, Farmington, N.M. 87499		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990 FNL and 2235' FWL		8. FARM OR LEASE NAME Dry Creek	
14. PERMIT NO.		9. WELL NO. 4	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6804 Gr		10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 36, T25N, R11W	
		12. COUNTY OR PARISH San Juan	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Set bridge plug at 5160' and spot 25 sks cement on top
2. Roll hole with 9.2 # mud
3. Perforate Cliffhouse at 3070' and cement inside and outside 4 1/2" casing from 3070' to 2970', 25 sks.
4. Chacra perf. 2375' set 25 sk plug inside and out of 4 1/2" casing 2375' to 2275'
5. Pictured Cliffs and Fruitland perf. 1660' set 25 sk plug inside and out of 4 1/2" casing 1660' to 1500'
6. Ojo Alamo perf. 860' set 40 sk plug inside and out of 4 1/2" casing 860' to 650'
7. Surface perf 256' set 25 sk plug inside and outside 4 1/2" casing 256' to 156'
8. Top plug 50' - 0 cement inside and out 4 1/2" casing 10 sks.
9. Erect dry hole marker
10. Clean location and seed to specifications

RECEIVED  
NOV 16 1987  
OIL CON. DIV.  
DIST. 2

I hereby certify that the foregoing is true and correct.

*W. M. Galloway*  
W. M. Galloway

Engineer

APPROVAL, IF ANY:

TITLE:

DATE 11-9-87

NOV 11 1987  
*John Skell*  
FARMINGTON RESOURCE AREA

See Instructions on Reverse Side

NMOCC