Form 9–331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42–R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM 25448

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.	7. UNIT AGREEMENT NAME
OIL WELL ☐ GAS WELL ☒ OTHER	

2. NAME OF OPERATOR

Hixon Development Company

8. FARM OR LEASE NAME
Federal 20

3. ADDRESS OF OPERATOR

P.O. Box 2810, Farmington, New Mexico 87401

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790' FNL, 790' FEL, Section 20, T25N, R12W

10. FIELD AND POOL, OR WILDCAT
Chacra – Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 20, T25N, R12W

14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
	6281' GLE	San Juan	NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) Drilling Progress ☒	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/06/80: Depth 82'. Spud well at 10:58 am 5/6/80. Drilled 9" hole to 82' with starch and water. Ran 78.65' new 7" 8rd 20# K-55 R-3 to 80' GLE. Cementers, Inc. circulated Class B cement with 2% CaCl and 1/4#/sack cellophane flakes to surface after 35 sacks. Displace cement from casing with water. Shut well in. WOC.

18. I hereby certify that the foregoing is true and correct

SIGNED _[signature]_ TITLE Petroleum Engineer DATE 5/9/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

See Instructions on Reverse Side