DEPARTME BUREAU OF SUNDRY NOTICES Do not use this form for proposals to de	ITED STATES NT OF THE INTERIOR LAND MANAGEMENT S AND REPORTS ON WELLS Irill or to deepen or reentry to a different reservoir. OR PERMIT—" for such proposals	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM 25447 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE 1. Type of Well		7. If Unit or CA, Agreement Designation
Other		8. Well Name and No.
2. Name of Operator		Bisti Coal 19 #1
Giant Exploration & Productio 3. Address and Telephone No.	n Company	9. API Well No.
PO Box 2810, Farmington, N.M.	07/00 (505) 00(0007	30-045-28142
4. Location of Well (Footage, Sec., T., R., M., or Survey I	87499 (505) 326~3325	10. Field and Pool, or Exploratory Area
1850' FNL, 790' FEL, Sec. 19,		Basin Fruitland Coal 11. County or Parish, State
CUECK ADDDODDIATE DOM		San Juan, New Mexico
CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Charact Phase

Subsequent Report

Final Abandonment Notice

New Construction

Water Shut-Off

Dispose Water

Non-Routine Fracturing

Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Recompletion

Plugging Back

Casing Repair

Altering Casing

XX Other Drilling Progress

Drilled out from under casing with 6-1/4" bit September 10, 1990. Drilled to TD of 1400'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 1056', Basal Fruitland Coal - 1249', Pictured Cliffs -1305'. Ran 33 jts. (1392.12') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1387.71', PBD at 1348.44'. Cemented casing as follows: Mixed and pumped 75 sks. (154.5 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

. I hereby certify that the foregoing is true and correct	A	OCT 9 1990
Signed Chis space for Fetteral or State of the USE F at Mon	1 pm President	ACCEPTED FOR RECORD
Approved by	Title	004 23 1990
		FARMINGTON RESOURCE AREA