

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☒ other
2. NAME OF OPERATOR
Consolidated Oil & Gas
3. ADDRESS OF OPERATOR
1860 Lincoln Street, Denver Colorado 80295
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **1120' FSL & 1600' FEL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) **Casing & Cement**

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-0117074-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Mills
9. WELL NO.
1E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 19 T25N R9W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6705' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-18-80 Spud 12 1/4" surface drilled to 277'. Ran 7 jts 8 5/8" 20# ST&C casing set at 276.33'. Cemented w/200 sx Cl "B" containing 2% CaCL. Circ 30 sx cement.

9-27-80 Drilled 7 7/8" at 6700'. Dresser Atlas ran IES FDC-CNL/GR/SP

9-29-80 Ran 4 1/2" 10.5# K-55 ST&C casing 152 jts with DV tools at 621' & 2057'. Cemented 1st stage w/330 sx 50-50 poz & 2% gel. Cemented 2nd stage w/350 sx 65-35 poz & 6% gel & 1/4# flocele per sx. Cemented 3rd stage w/485 sx 6 5-35 poz & 6% gel & 1/4# flocele per sx. Circ 25 BBL cement to surface.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE **Drilling Supt.**

DATE **9-29-80**

(This space for Federal or State office use)

APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

TITLE _____

DATE _____

OCT 08 1980

*See Instructions on Reverse Side

BY

[Signature]
BIRMINGHAM DISTRICT

NMOCC