

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Consolidated Oil & Gas

3. ADDRESS OF OPERATOR
1860 Lincoln Street, Denver Colorado 80295

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **1120' FSL & 1600' FEL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) **Casing & Cement**

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-0117074

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mill

9. WELL NO.
1E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec19 T25N R9W

12. COUNTY OR PARISH **San Juan** 13. STATE **New Mexico**

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6705' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-18-80 Spud 12 1/4" surface drilled to 277'. Ran 7 jts 8 5/8" 20# ST&C casing set at 276.33'. Cemented w/200 sx G1 "B" containing 2% CaCL. Circ 30 sx cement.

9-27-80 Drilled 7 7/8" at 6700'. Dresser Atlas ran IES FDC-CNL/GR/SP

9-29-80 Ran 4 1/2" 10.5# K-55 ST&C casing 152 jts with DV tools at 621' & 2057'. Cemented 1st stage w/330 sx 50-50 poz & 2% gel. Cemented 2nd stage w/350 sx 65-35 poz & 6% gel & 1/4# flocele per sx. Cemented 3rd stage w/485 sx 6 5-35 poz & 6% gel & 1/4# flocele per sx. Circ 25 BBL cement to surface.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE **Drilling Supt.**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

