

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Consolidated Oil & Gas, Inc.  
3. ADDRESS OF OPERATOR  
PO Box 2038, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1850' FNL & 1840' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Casing &amp; Cement</u>	

5. LEASE  
013480  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Ladd  
9. WELL NO.  
1-E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 19 T25N R9W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6747' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-15-80: Drilled 12 1/4" surface to 260'. Ran 6 jts. 8 5/8" 20# H-40 casing. Cemented at 254' with 200 sx class "B". Circ. 5 bbl. of cement to surface.

11-24-80: Drilled 7 7/8" hole to 6582'. Schlumberger ran IES, FDC, CNL/GR.

11-25-80: Ran 166 jts. 5 1/2" 15.5# K-55 ST&C. Cemented at 6580'.  
1st stage - 350 sx 50-50 POZ & 2% Gel. Cemented 2nd stage -  
185 sx Howco Lite. Cemented 3rd stage - 400 sx Howco Lite  
DV tools at 4691' & 2620'. Top of cement by temperature survey  
500' from surface.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Supt. DATE 11-26-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 04 1980

FARMINGTON DISTRICT

\*See Instructions on Reverse Side

NMOCC

