334-6170

TO FFH

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS (EN

- 1	# 1FACE	- ラノコ
	5. LEASE NOOC-14-20-3604	537
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	55
	Rena Etsitty	
W	STAUNIT AGREEMENT NAME	
rent I		
199	FARM OR LEASE NAME	
IU J	Contiton	
M	9. WELL NO.	
1	44/0	
<u></u>	10. FIELD OR WILDCAT NAME Basin Dakota	
	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
	AREA	
17	Sec 5 T25N RllW	
	12. COUNTY OR PARISH 13. STATE	
	San Juan New Mexico	
	14 48/310 3	
ÇE.	30-045-24.786	
·	15, ELEVATIONS (SHOW DF, KDB, AND WD)	
ممير	(d320' dr.	
الله	(NOTE: Recall result of multiple completion or zone	
	(NOTE: Receive results of multiple completion or zone of age of Forin 9-330.)	
Market Street		
lis	ite all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*	
ut .	and shoe. Drill to 5960'. Tennec	: Q
		id
	shandon Spotted blugs as follow	/S 1

AREA MANAGER

(Do not use this form for proposals to dritt or to deepen of plug back to a difference.) Use Form 9-331-C for such proposals.) well other well 2. NAME OF OPERATOR Tenneco Oil Company 3. ADDRESS OF OPERATOR Box 3249 Englewood, Co 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space below.) 870' FNL 1660' FWL "C" AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOT REPORT, OR OTHER DATA SUBSEQUENT REPORT OF REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* v (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly including estimated date of starting any proposed work. If we measured and true vertical depths for all markers and zones pe 1/28/81. PT to 600PSI for 15 mins. Drill co has elected not to run csg over Dakota zone. down drill collars. TIH open ended to plug and a Spotted binds Release rig. Install P & A marker. 2/7/81. 5763-5598' 165' 30 sx cmt. #1 - Dakota Approved as to plugging of the wall but. #2 - Mesaverde 4965-4635' 330' 60 sx cmt. Elability under bond is retained until #3 - Pictured Cliffs 2302-2082' 220' 40 sx cmt. serface adaloration is completed. 165' 30 sx cmt. #4 - OJO Alama 1370-1205' 217' 60 sx cmt. 567 -167-1501 #5 - Shoe 0-30' 30' 10 sx cmt. #6 - Surface Set @ Subsurface Safety Valve: Manu. and Type ... certify that the foregoing is true and correct Asst.Div.Adm.Mgr. DATE Februa (This space for Federal or State office use) 14/8 12/14/8 DATE APPROVED BY CONDITIONS OF APPROVAL IF ANY:

an Reverse Side