

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

N00-C-14-20-5246

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NAVAJO ALLOTTED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

AH-NUS-BAH

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T25N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER **P & A**

2. NAME OF OPERATOR

LUDWICK EXPLORATION COMPANY

3. ADDRESS OF OPERATOR

P.O. Box 70

Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1840'FWL, 1010'FSL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6485 Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and bones pertinent to this work.) *

TD 1900, PB 1860 WO approval to P & A.


1. Will place 35' cement on top of BP @ 1730.

2. Will fill 2-7/8 production casing with cement,
by pumping 25% over capacity into perfs 1639-66.

3. Attempt to back off top joint of production casing
and place 30' cement plug between 2-7/8" casing and
7" surface casing.

4. Install marker and restore location.

VERBAL APPROVAL OBTAINED FROM RICHARD BELL on 4-29-1981.



18. I hereby certify that the _____ is true and correct

SIGNED

Handwritten signature: Richard B. Kennedy

TITLE

Agent

DATE

4-30-1981

(This space for Federal or State use.)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side

APPROVED

MAY 8 1981

Handwritten signature: James F. Sims
FOR JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR