Form 9-331 (May 1963)	DEPAR [*]	UNITED STATES IMENT OF THE INT		SUBMIT IN TRIPLICATI (Other instructions on inverse side)	e- 5. 1.	EASE DESIGNATION	u No. 42-R1424.
(Do not	SUNDRY NC	OTICES AND REPORT OF THE CATION FOR PERMIT—" for s	TS ON	WELLS o a diffrent reservoir.		'-078530 f indian, allottee	OR TRIBE NAME
OIL WELL	GAS WELL X OTHER			Mary Grand Co.		UNIT AGREEMENT NA	
M. J.	OIL COM. COM.	F	ederal 20				
		uite 124, Ft. W <u>or</u>	th Tex	3618457 i		1-R	
4. LOCATION OF WELL (Report location clearly and in accordance with see also space 17 below.) At surface 1850'FSL, 1800'FEL			p les Ent	1	В	sec., T., B., M., OR B	ta
				JUL 1 0 1401 U. S. GEOLOGICAL SURVEY		Sec. 20-T25N-R9W N.M.P.M.	
14. PERMIT NO.		15. ELEVATIONS (Show wheth	her DF, PRICE	MINGJON, IV. M.	1	COUNTY OF PARISH	1
		6675 GL \-				an Juan	N.M.
16.	Check A	Appropriate Box To Indica	ate Natur	e of Notice, Report, or	Other	Data	
	NOTICE OF INT	ENTION TO:		SUBSI	QUENT F	REPORT OF:	
TEST WATE	R SHUT-OFF	PULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRING W	ELL
FRACTURE	TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	SING
SHOOT OR		ABANDON*		SHOOTING OR ACIDIZING		ABANDONMEN	T*
(Other)	LL	CHANGE PLANS		(Other)	ts of m	ultiple completion of Report and Log for	on Well m.)
proposed	OPOSED OR COMPLETED O work. If well is direction ois work.) *	PERATIONS (Clearly state all per tionally drilled, give subsurface	rtinent det e locati ons	alls, and give pertinent date and measured and true vert	s, inclu ical dep	ding estimated date ths for all markers	of starting any and zones perti-
nem to u		AMENDED	REPOR'	<u>r</u>			
6/13/81		. Ran 175 join set at 6609.13			11.6	10, K-55 c	asing
	First Stag			Pozmix with 6- per sack. Cal			
	Second Sta		er sa	Pozmix (12% G ck followed by age Collar 471	50	·	

FOR: M. J. BRANNON

Third Stage:

18. I hereby certify that the for GRIGINALUSIONED BY SIGNED EWELL N. WALSH EWELL N. WALSH, P.E.	TITLE	President, Walsh Engr. & Production Corp.	DATE _	7/8/81
(This space for Federal or State office use)				
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	acetic 1	D ATE	<u> </u>

510 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs.

Gilsonite per sack followed by 50 sacks Class "B" Neat Cement. Cement circulated to surface. Stage Collar 2184'.

*See Instructions on Reverse Side

SOOner

