

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078056

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

PT

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated - PC

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 7, T25N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1. OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

2. NAME OF OPERATOR

Dugan Production Corp.

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

990' FNL - 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6248' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2-1-76

Moved in and rigged up Morrow Drilling Company Rig #1 and drilled 7-7/8" hole to 34'.  
Ran one jt 5-1/2" OD 14# J-55 "B" condition csg set @ 33' GR, cemented w/5 sx. Job  
complete 12:01 PM 1-31-76.

2-8-76

TD 1335'. Finished drilling 4-3/4" hole to driller's TD 1335', conditioned hole,  
laid down drill pipe, and ran IES log by Welex (logger's TD 1337'). Ran 44 jts  
2-7/8" OD 6.5# 8R EUE "B" condition tbq for csg, TE 1335.34' set @ 1334' GR, ce-  
mented by BJ w/75 sx 2% Lodense with 1/4# Cello-flake/sk, good mud returns while  
cementing. Max cementing press 750 psi, reciprocated pipe while cementing, left  
shut in w/1000 psi. POB 6:15 PM 2-7-76.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

2-9-76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

FEB 10 1976

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY