

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS


(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Tesoro Petroleum Corporation
3. ADDRESS OF OPERATOR  
633 17th St., Ste 2000, Denver, CO 80202
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)  
AT SURFACE: 800' FNL X 1820' FWL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
- FIRST WATER SHUT-OFF ☐
- PERFORATE TRAIL ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- REINFORCE OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON ☐
- (other) Drill & run prod. csg. ☒ /X/

5. LEASE  
N00-C-14-20-5210
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Jaquez
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 6-T25N-R11W
12. COUNTY OR PARISH  
San Juan
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6203' GL, 6208' KB

(NOTE: Report results of multiple completion zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drill out surface csg. cement and begin drilling 6 1/4" hole at 1:00 AM 8/31/81. Drill to TD of 1300' (KB) on 9/2/81. Ran DIL-GR-SP and CNL-FDC-GR-CAL. logs from TD to 231 ft. Ran 1301.66 ft. of 4 1/2", 10.5# casing and set at 1300 ft. (KB) and cemented w/60 sks. class "G" w/0.5% calcium chloride (9/2/81). Full returns throughout cement job. Calculated cmt. top at 800 ft. Prepare to perforate and fracutre stimulate Pictured Cliffs formation at 1145-1155 ft. (KB).

Subsurface Safety Valve: Manu. and Type None Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Parks DIST. Oper. Mgr. DATE 9/3/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC