

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
KM Production Company
3. ADDRESS OF OPERATOR
P.O. Box 2406, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840' FNL & 790' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Spud, cement surf. csg.	

5. LEASE
NOO-C-14-20-5245
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Allottee
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
FBD Com
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Bisti Lower Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 21, T25N, R11W
12. COUNTY OR PARISH
San Juan
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6448' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04-20-82 Spud at 5:30 p.m. on 04-19-82. Drilled 224 ft. of 12-1/4" hole. Ran 223 ft. of 8-5/8", 24#/ft., J-55, new casing. Set casing at 223 ft. RKB. Rigged up Cementers Inc. and cemented surface casing with 125 sacks Class "B" cement with 2% CaCl. Good circulation throughout job. Circulated 30 sacks of cement to surface. Plug down at 11:00 p.m. 04-19-82. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Operator DATE April 20, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMOCC

APR 21 1982

FARMINGTON DISTRICT

BY [Signature]