Form 3 60-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir,

FORM APPROVED
Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No. SF 078056

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Use "APPLICATIO	ON FOR PERMIT" for such p	proposals 37 20 20	
SUBMIT II	N TRIPLICATE	2500	Central Bisti Unit
1. Type of Well  X Oil Well Ga	s Well Other	AUG 2000	8. Well Name and No.
2. Name of Operator Central Resources, Inc.		S PE	9. API Well No. 30-045-25343
3. Address and Telephone No. P.O. Box 1247, Bloomfield, New	Mexico 87413 (505)-632	2\3476	10. Field and Pool, or Exploratory Area Bisti Lower Gallup
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 560' FNL, 1980' FEL, Sec 6, T25N, R12W			11. County or Parish, State San Juan County, New Mexico
2. CHECK APPROPRIATE BOX(s) TO	INDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	1
	X Abando	nment	Change of Plans
X Notice of Intent	Recomp	oletion	New Construction
	Pluggin	g Back	Non-Routine Fracturing
Subsequent Report	Casing	·	Water Shut-Off
[oubsequent report		g Casing	Conversion to Injection
Final Abandonment Notice	Other		Dispose Water
			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (	Clearly state all pertinent dates, in	ncluding estimated date of starting	any proposed work. If well is

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Central Resources, Inc. intends to plug the well in accordance with regulations. Production equipment will be removed and the well will be plugged as specified. Perforate and squeeze will be used unless casing can be recovered over the specified interval or there is evidence cement is in place behind the casing.

Proposed procedure:

- a. Notify the Farmington BLM office at 505-599-8907 24 hours prior to commencement of plugging operations.
- b. Pull all retrievable downhole production equipment.
- c. Set a CIBP at 4800' and spot 50' of cement on top.
- d. Set a 100' cement plug from 2534' to 2634' across Menefee top at 2584'.
- e. Set a 100' cement plug from 1079' to 1231' across the Fruitland at 1119' & Pictured Cliffs at 1181'.
- f. Set a 100' cement plug from 166' to 266' across the surface casing shoe at 216'.
- g. Set a 50' cement plug from surface to 50'.
- h. Cut wellhead and install dry hole marker. Clear and remediate location.

Please take into account the number of existing P&A procedures, the number of P&A procedures you have requested and the available equipment and allow Central Resources, Inc. until the end of 2001 to complete this abandonment.

4. I hereby certify that the foregoing is true and corresponded	Title District Manager	Date	June 27, 2000
Rodney L. Selle			
(This space for Federal or State office use) approved by	Title	Date	8/23/00
Conditions of approval, if any:			

fictitions or fraudulent statements or representations as to any manner within its jurisdiction.

\*See Instruction on Reverse Side

## CENTRAL RESOURCES, INC.

## Central Bisti Unit No. 80

5-6-00 by Rod Seale Review Date: Elevation: 6171' GL, 6184' KB Location: 660' FNL, 1980' FEL, Sec 6, 25-N, 12-W, San Juan County, New Mexico Field: Bisti Lower Gallup 8 5/8" 24# K55 CSA 216' w/ 130sx Zone: Lower Gailup Perfs: 4817' - 4843' Spud Date: May 26, 1982 12:00 AM 3 1/2" scab liner 2054' to 3610' on 5 -95 Inspection log indicate bad casing 2650' to 3000' on 4-87 Bottom of liner at 3610' TOC is 3710' by CBL Tbg - unknown, possible 2 3/8" & 2 1/16" w/ rods & pump Perf JSPF over 4817-43 PBTD: 5006' 4 1/2" 10.5# K55 CSA 5068' w/ 450 sx 5090' - TD: