

Form 3160-5
(June 1990)

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill for or deepen or re-enter a different reservoir.

Use APPLICATION FOR PERMIT-2 for such proposals.

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No.

SF-078056

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

Central Bisti *isnt*

1. Type of Well

☐

Oil Well

☐

Gas Well

☒

Other

2. Name of Operator

Central Resources, Inc.

3. Address and Telephone No.

P.O. Box 1213, Bloomfield, New Mexico 87413 (505) 833-3410

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL, 2300' FWL, Sec 6, T25N, R12W

8. Well Name and No.

WI-78

9. API Well No.

,30-045-25345

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐

Notice of Intent

☐

Subsequent Report

☒

Final Abandonment Notice

☒

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☐

Other

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

January 20-23, 2001

A. Cover the top of the Gallup plug to 4761' using 20 sacks cement.

B. Cover top of Mesa Verde plug from 1875' to 1975' inside and outside the 4 1/2" casing using 45 sacks cement.

C. Set Pictured Cliffs plug from 1148' to 1248' inside and outside the 4 1/2" casing using 45 sacks cement.

D. Place the Fruitland plug from 866' to 766' inside and outside the 4 1/2" casing using 45 sacks cement.

E. Place the surface plug from 266' to surface inside and outside the 4 1/2" casing to cover the surface casing shoe, the Ojo Alamo interval with 150 sacks.

Patty Shelton

Title Production Tech.

Date

February 12, 2001

14. I, Patty Shelton

Si (This space for Federal or State office use)

Title

Date

Conditions of approval, if any:

Approved by

COPIED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for a
fictitious or fraudulent statements or representations as to any manner within its jurisdiction.

*See Instruction on Reverse Side

FEB 13 2001

NMOCD

San Juan Office

X