

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Hixon Development Company
3. ADDRESS OF OPERATOR  
P.O. Box 2810, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL, 1650' FWL 15-25N-12W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒

(other) Drilling Report

SUBSEQUENT REPORT OF

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
JAN 21 1983  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
NM 070322
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Carson Unit
8. FARM OR LEASE NAME
9. WELL NO.  
204
10. FIELD OR WILDCAT NAME  
Pictured Cliffs - WAW
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 15-T25N-R12W
12. COUNTY OR PARISH  
San Juan
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6250' GLE . 6254' KB

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drill out from under surface with 5-1/4" bit. 1210' TD. Reached 1/24/83  
is as follows: 1/2° at 650', 3/4° at 1022'. Ran Induction Electric Deviation  
and Compensated Density Neutron logs. Log tops as follows: Pictured  
Cliffs - 1039', Fruitland Coal - 1022', Fruitland - 796', Base of Ojo  
Alamo - 143'. Obtained verbal approval to plug and abandon well from  
Ken Townsend, BLM. Spot cement plugs as follows: Plug #1, 1100'-900'  
with 25 sacks; Plug #2 850'-650' with 25 sacks, Plug #3, 400' to surface  
with 55 sacks.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Adrian W. Anderson TITLE Petroleum Engineer DATE 1/27/83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions on Reverse Side

NM000

APPROVED  
AS AMENDED

FEB 2 1983  
JAMES F. SIMS  
DISTRICT ENGINEER