Form 3160-5 (November 1983) (Formerly 9-331)

10

UNITED STATES SUBMIT IN TRIPLICATE® (Other instructions on reverse side) BUDGALLOG LAND MANAGEMENT

6500' K.B.

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

TRIBE NAME

N.M.

5. LEASE DESIGNATION AND SERIAL NO.

NOO-C-14-20-5249

SAN JUAN

BUNEAU OF EARLY MANAGEMENT	1 1100-0-14-20-024
INDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR

(I)o not use this form for propo	ICES AND REPORIS ON WELLS sals to drill or to deepen or plug back to a different reservoir. ATION FOR PERMIT—" for such proposals.)	ALLOTTEE
OIL CAB OTHER		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR COLEMAN OIL AND GAS,	INC. Coronade Magnit Corp.	8. FARM OR LEASE NAME BISTI
	ARMINGTON, N.M. 8740RFCFIVFD	9. WBLL RO.
4. LOCATION OF WELL (Report location of See also space 17 below.) At surface	APR 0.8 1987	10. FIELD/AND POOL, OR WILDCAT BISTI: LOWER GALLUP
2090' FSL & 1960' FWL	BUREAU OF LAND MANAGEMENT	11. SBC., T., R., M., OR BLK. AND BURNEY OR ARBA SEC. 23, T 25N, R 11W NMPM
14. PERMIT NO.	15. BLEVATIONS (Show whether ARM) NETON, RESOURCE AREA	12. COUNTY OR PARISH 13. STATE

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF		PORT OF:			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CABING
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT* XX
REPAIR WELL		CHANGE PLANS		(Other)	
(Other)				(Nors: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) *

ON 3-25-87 THE SUBJECT WELL WAS PLUGGED AS FOLLOWS. SET BRIDGE PLUG AT 4902'. FILLED HOLE WITH MUD AND SPOTTED A 35 SACK CEMENT PLUG ON TOP OF BRIDGE PLUG. SPOTTED 10 SACK CEMENT PLUGS AT 2803', 1750', 1418' AND 1122'. PERFORATED 4 HOLES AT 600'. CIRCULATED WITH BRADENHEAD. PUMPED 90 SACKS OF CEMENT. PLUG FROM 270' TO 600' INSIDE AND OUTSIDE 41/2" CASING. SPOTTED 5 SACKS OF CEMENT FROM 50' TO SURFACE.

ON 3-26-87 INSTALLED DRY HOLE MARKER.

> Approval a la bi-Liability Co. ... Surface retitionaled at a

18. I hereby certify that the foregoing is true and correct Presiden SIGNED TITLE (This space for Federal or State office use) APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY: 15. A. S. S. S. *See Instructions on Reverse Side