

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Horonango Land, Inc. Corporation

3. ADDRESS OF OPERATOR 5704 Villa View Drive
c/o R. Simmons Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 740' FSL & 1860' FSL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Completion Operations ☒

5. LEASE

000-C-14-00-0000

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Albuquerque Indian Reservation

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

1100

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Intl Lower Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T25N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6498' DF (6510' KB)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-7-83 Moved completion tools on location. Cleaned out cement in 5 1/2" casing to FBTD & 5040' KB. Pressure tested casing to 3000 psi. OK. Circ. hole w/ 2 1/2" bit. Shot 500 gals. 10% acetic acid.

7-10-83 Ran CBL-31-CCH from FBTD to D.V. tool at 3895' in. Cement to 3912' KB. Perf. 5004-10' w/ 2 1/2" (12 holes) & 1 ea. 4 1/2" 4877, 4934. Pumped acid in perf. w/ 45,000 # 10/20 sand in 70% foam using 530,000 SCF. Cement well to bit.

7-11-83 Ran tubing in hole & cleaned out to 110'. Ran tubing in hole and landed with bottom at 4940' in. 2 1/2" ID w/ wellhead.

7-16-83 Ran rod pump and rods. Rigged down rd.

7-18-83 Moved rd. on location. (7-12 thru 7-15-83) Set production equipment. Turned well on production 7-15-83.

Subsurface Safety Valve: Manu. and Type

Set @

ft

18. I hereby certify that the foregoing is true and correct

SIGNED

R. D. SIMMONS

TITLE

DATE

7-16-83

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

ACCEPTED FOR RECORD

SEP 30 1983

FARMINGTON RESOURCE AREA

BY

SJM

*See Instructions on Reverse Side

NMOCC

ILLECIBLE