5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

ONTED STATES) J. LEASE
DEPARTMENT OF THE INTERIOR	√ N00-C-14-20-5250
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Allottee Mar-Ga-Le-Ta
SUNDRY NOTICES AND REPORTS ON	WELLS 7. UNIT AGREEMENT NAME
SUNDRY MUTICES AND INC. ON 10 deepen or plug had	k to a different
(Do not use this form for proposals to drill or to deepen or plug bac reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
	Bisti
1 oil gas	9. WELL NO.
Well	2
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
Coronado Management Corporation	Digti Torrom Callum
3. ADDRESS OF OPERATOR Farmington, No R.D. Simmons 5704 Villa View D	11. SEC., T., R., M., OR BLK. AND SURVEY OR
c/o R.D.Simmons 5704 Villa View D	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY.	23, T25N, R11W
below.)	12. COUNTY OR PARISH 13. STATE
AT SURFACE: 740' FSL 1860' FEL	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE	OF NOTICE,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6498' GR (6510' KB)
REQUEST FOR APPROVAL TO: SUBSEQUENT RE	PORT OF:
TEST WATER SHUT-OFF	
FRACTURE TREAT	CEIVED DECEIVED
SHOOT OR ACIDIZE	NIC 3 0 1983 (NOTE: Report A lits of multiple completion or zace
PULL OR ALTER CASING	change in Form 9–330.)
	DE LAND MANAGEMENT SEP 1=1983
	TON RESOURCE AREA
ARANDON*	OIL CON. DIV.
(other) Spud date and surface casi	ng and cement DIST. 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATION	S (Clearly state all pertinent details, and give pertinent dates, ork. If well is directionally drilled, give subsurface locations and
measured and true vertical depths for all markers and	zones pertinent to this work.)*
August 24, 1983. Four Corner	s Drilling Co. Rig #2 moved on
location. Spud weel at 1:00 PM. Drilled	
12½" mud ho	Dle to 312' KB. Ran 7 joints 8-5/8"
24#, K55, R3, STC casing (298.191). Set	
casing with bottom at 312' KB. Cemented with	
210 sacks (247.80 cu. ft.) Glass "B" with	
1//# per sack flocele and 2% CaClo. Circulated	
5 barrels cement to surface. Plug down at	
7:00 PM 8-	24-83. Woc 12 hours.
August 25, 1983 Pressure te	est casing and BOP to 600 PSIG. Held
J	
17.5	Set @ Ft.
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	
	rent August 25, 1983
	gent DATE August 25, 1983
	ederal or State office use)
APPROVED BYTITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
	ACCEPTED FOR DECORD
	ACCEPTED FOR RECORD

*See Instructions on Reverse Side

AUG 3 1 1983

FARMINGIUN RESOURCE AREA