## Form Approved. Budget Bureau No. 42-R1424

DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	5. LEASE NM- 31311  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Champlin Federal
1. oil gas other	9. WELL NO. #1
2. NAME OF OPERATOR Southern Union Exploration	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 2179, Farmington, NM 87499	Bisti Lower Gallup  11. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec 11-T25N-R13W,NMPM
AT SURFACE: 660' FNL & 660' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Juan Co, New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD 6293' GL

SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* Spud and Set Surface Casing (other)

SEP 8 - 1983

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud 12 1/4" surface hole @ 6:30 p.m. 8-26-83. Drilled 12 1/4" Set 7 jts. 8 5/8" 32.0# ST&C K-55 casing hole to 298'(Dev. 3/4°). Cemented with 265 ft Class B cement with 2% CaCl, and 1/4#/sk flocele. Plug down @ 12:15 a.m. 8-27-83. Good circ thruout. RU BOP and pressure test 800 psi for 30 WOC 12 hrs. Circ 15 bbls. min. OK.

Subsurface Safety Valve: Manu. and	Гуре	Set @	. Ft.
18. I hereby certify that the foregoing	g is true and correct  TITLE Drlg & Prod. Spy	ser. 9-6-83	
_//	(This space for Federal or State office use)	ACHE TED FUR RECORD	,
APPROVED BY	TITLE	SEP-0 7 1983	

\*See Instructions on Reverse Side

 $\mathsf{NMU}_{\mathsf{Lit}}$