(other)

Form 9-331	Budget Bureau No. 4R. 4.4
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	<u>20-603-323</u>
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
dedeadone com	Navajo Allotted
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to crill or to deepen or plug back to a different	Central Bisti Lower Gallup Unit
(Do not use this form for proposals to Critical to describe the form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil - gas -	
well well other	9. WELL NO.
2. NAME OF OPERATOR	84
Hixon Development Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Bisti Lower Gallup
P.O. Box 2810, Farmington, NM	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
helow.)	Section 5, T25N, R12W 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 1200' FSL, 720' FEL, 5-25-12	1
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan NM
	14. AFI NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6163' GLE
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	

SHOOT OR ACIDIZE F C F | VNOTE REPORT results of multiple completion or zone change on Form 9–330.) REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

Progress

BUREAU OF LAND MANAGEMENT FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well at 2:45 pm 10/8/83. Drill 12-1/4" hole to 220. Run 201.52' 8-5/8" 24# K-55 8rd surface casing. Install guide shoe on shoe joint and centralizers on tops of 1st and 3rd joints. Casing set at 216.50'. Cement surface casing using 135 sacks (159.3 cubic feet) Class B with 2% CaCl. Cement circulated to surface. Shut well in. WOC.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. hereby certify that the foregoing is true and correct SIGNED TO TO THE ENGINEER DATE.	10/10/83	
(This space for Federal or State office use)		
APPROVED BY DATE CONDITIONS OF APPROVAL, IF ANY:	ACCEPTED FOR RECORD	

*See Instructions on Reverse Side

FARMINGION RESUUNCE AREA BY Sinh

OCT 24 1983

Form Approved.