6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Thomason Killyoner MKEA

5 mm

5. LEASE

SF078056

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND BEPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill to deepen or plug back to a different reservoir. Use Form 9-331-C for such profile 11.	Central Bisti Lower Gallup Uni
	8. FARM OR LEASE NAME
1. oil gas well other other	
	9. WELL NO.
2. NAME OF OPERATOR	97
Hixon Development Offgrany  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME
P.O. Box 2810, Farmington, NM	Bisti Lower Gallup  11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	<b>~</b> F
below.)	Section 7. T25N, R12W
AT SURFACE: 2310' FSL, 1650' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: 7-25-12	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6297' GLE •
TEST WATER SHUT-OFF	
EPACTURE TREAT	
SHOOT OR ACIDIZE	IVED
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	3 1984 change on Form 9–330.)
CHANGE ZONES   BUREAU OF LAME	
ABANDON* EARMINGTON PE	SOURGE AREA
(other) <u>Drilling Progress</u>	
including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine Drill out from under surface casing wir 7-7/8" hole to a total depth of 5060'. Compensated Density Neutron logs. Log Gallup 4850', Upper Gallup 4760', Upper Gallup 4760', Upper Lookout 3678', Menefee 2540', Cliffhous Pictured Cliffs 1200'. Run 5040' 5-1/3 casing to 5052'. Cement casing with 69 feet) of Class B cement. Dropped plug BW. Circulated 19 barrels of cement to on completion.	th 7-7/8" bit 4/3/84. Drill Run Gamma Induction and tops as follows: Lower r Mancos 3844', Point se 1550', Lewis 1364', 2" 15 5# K-55 8rd ST&C 00 sacks (1312 cubic and displaced with 119
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Bruce Delventhas TITE etroleum End	ginee <sub>Fate</sub> 4/17/84
(This space for Federal or State of	ffice use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	ACCEPTED FOR RECORD
	MAY 1-0 1984
	to the first of the control of the state of the control of the co

\*See Instructions on Reverse Side