

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
-
2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.
-
3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499
-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1090' FNL - 790' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
-
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- REQUEST FOR APPROVAL TO:
- | | |
|----------------------|-------------------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> |
| ABANDON* | <input checked="" type="checkbox"/> |
| (other) _____ | |

- SUBSEQUENT REPORT OF:

RECEIVED

OCT - 9 1954

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
NM 37907
-
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-
7. UNIT AGREEMENT NAME
-
8. FARM OR LEASE NAME
Corral
-
9. WELL NO.
1
-
10. FIELD OR WILDCAT NAME
Undesignated Pic. Cliffs
-
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 23, T25N, R9W, NMPM
-
- | | |
|----------------------------------|-----------------|
| 12. COUNTY OR PARISH
San Juan | 13. STATE
NM |
|----------------------------------|-----------------|
-
14. API NO.
-
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6500' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug and abandon well as follows:

1. Spot 100' cement plug 1870 - 1770'.
2. Spot 100' cement plug 1628 - 1528'.
3. Spot 100' cement plug 1066 - 966'.
4. Spot 147' cement plug 147' to surface.
5. Install dry hole marker and restore surface.

*VERBAL INSTRUCTIONS OBTAINED FROM STEVE MASON - BLM 10-5-84.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 10-5-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

RECEIVED

OCT 15 1984

OIL CON. DIV.

DIST. 3

/s/ J. Stan McKee

AREA MANAGER
FARMINGTON RESOURCE AREA

NMOCC