

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1090' FNL - 790' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

OCT - 9 1984

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

5. LEASE  
NM 37907

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Corral

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Undesignated Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 23, T25N, R9W, NMPM

12. COUNTY OR PARISH | 13. STATE  
San Juan | NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6500' GL

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10-5-84 Reached TD of 1975'

Plugged and abandoned well as follows: T.I.H. with drill pipe open ended. Spotted 12 sx cement plug (14.16 cu. ft.) 1870' to 1770'; spotted 12 sx cement plug (14.16 cu. ft.) 1628' to 1528'; spotted 12 sx cement plug (14.16 cu. ft.) 1066' to 966'; spotted 32 sx cement plug (37.76 cu. ft.) 147' to surface. Installed dry hole marker. Pits are fenced and will be filled and surface restored when pits have dried. (Note - plugging instructions obtained from Steve Mason 10-5-84.) Work completed 3:30 p.m. 10-5-84.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 10-8-84  
(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY.

TITLE DATE

Set @ **APPROVED**

OCT 11 1984

W. J. Stan McKee  
AREA MANAGER  
FARMINGTON RESOURCE AREA