

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM - 58138	
2. NAME OF OPERATOR CORRIDA OILS INC.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 5550 T. A., Denver, CO 80217		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface  660' FSL & 660' FEL Sec. 12-T25N-R13W		8. FARM OR LEASE NAME Bad Lands Federal	
14. PERMIT NO.		9. WELL NO. #2	
15. ELEVATIONS (Show whether OF, RT, OR, etc.) 6479 GL		10. FIELD AND POOL, OR WILDCAT Bisti Lower Gallup	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12-T25N-R13W NMMPM	
		12. COUNTY OR PARISH 13. STATE San Juan NM	

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐  
☐  
☐  
☐

PULL OR ALTER CASING

☐  
☐  
☐  
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐  
☐  
☐

REPAIRING WELL

☐  
☐  
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other) Commencement of Drilling

☒

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well on Nov. 27, 1984 at 9:00pm. Drilled 12 1/4" hole to 314 R.K.B. Ran 7 jts. 8 5/8", 24#, ST & C csg. to 308' R.K.B. Cemented csg. with 210 sx. (247.8 cu.ft.) of Class "B" neat with 2% Cacl. Circulated 14 sx. (16.5 cu.ft.) of cement to surface. P.O.B. at 4:00am Nov. 28, 1984. W.O.C. - 12 hrs. slurry temp. - 70°F, bottom hole temp. - 80°F. Compressive strength of cement after 12 hrs. - 1675psi. Pressure tested csg. to 1000psi for 30 mins., held O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE Geologist

DATE Dec. 6, 1984

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

DEC 11 1984

\*See Instructions on Reverse Side

NMOCO

FARMINGTON RESOURCE AREA

BY