	UNITED STATES SUBMIT IN TRIPLICA: Other instructions on BUREAU OF LAND MANAGEMENT	5. LEASE DESIGNATION AND SERIAL NO. NM 036253
	NDRY NOTICES AND REPORTS ON WELLS is form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL XX GAS WELL	OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
	Hixon Development Company	Mudge
3. ADDRESS OF OPERAT	OR .	9. WELL NO.
A LOCUMINA OF WELL	P.O. Box 2810, Farmington, NM 87499 (Report location clearly and in accordance with any State requirements.*	#8
See also space 17 be At surface		10. FIELD AND POOL, OR WILDCAT
At suitace		Bisti Lower Gallup 11. SEC., T., R., M., OR BLE. AND
	1980' FSL, 1770' FEL, Section 18 7 250 R 11W	SURVEY OR AREA
	***************************************	Section 16, T 25N, R 11
14. PERMIT NO.	15. ELEVATIONS (Show whether my my on the management	12. COUNTY OR PARISH 13. STATE
	6395' GLE	San Juan New Mexico
16.	Check Appropriate Box To Indicate Nature of Notice, Report, o	or Other Data
		SEQUENT REPORT OF:
TEST WATER SHUT-	OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CABING
SHOOT OR ACIDIZE	ABANDON* SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANE (Other)	
(Other)	(NOTE: Report res Completion or Reco	uits of multiple completion on Well completion Report and Log form.)
nent to this work.	Spudded well at 8:15 PM on 3/5/85. Drilled 12-	1/4" hole to 476' K.B.
	Ran 11 joints (454.95') of 8-5/8" 24#, J-55, 8 casing. Installed cement nosed guide shoe on 1 on top of 1st, 3rd, and 5th joint. Set casing casing in hole with 250 sks (295 cuft.) of Clas 2% CaCl. Circulated cement to surface. Shut i Pressure tested surface casing to 600 psi.	st joint and centralizers at 470' K.B. Cemented s "B" cement containing

*See Instructions on Reverse Side

NMOCO SM