Form 3160-5

UNITED STATES

rorm approved. ∠ Budget Bureau No. 1004-0135

(November 1983) (Formerly 9–331) DEPARTMENT OF THE		CIOR (Other instructions on re-	Expires August 31, 1985	
BUREAU OF LAND MANAGEMENT			5. LEASE DESIGNATION AND SERIAL NO. 14-20-603-1343	
CULIDO	6. IF INDIAN, ALLOTTEE OR TEIDE NAME Navajo Allottee			
SUNDR (Do not use this form				
OIL GAS WELL WELL X	7. UNIT AGREEMENT NAME			
2. NAME OF OPERATOR	8. FARM OR LEASE NAME			
ARCO Oil and Gas	Navajo Allotted Com			
3. ADDRESS OF OPERATOR	9. WELL NO.			
P.O. Box 5540, D	1E			
4. COCATION OF WELL (Report location clearly and in accordance with any State requirements.			10. FIELD AND POOL, OR WILDCAT	
At surface			Basin Dakota	
1620' FSL & 860' FEL APR 101985			11. SEC., T., E., M., OR SLK. AND SURVEY OR AREA	
	· · · · · · · · · · · · · · · · · · ·	REAU OF LAND MANAGEMENT	24-25N-10W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)		12. COUNTY OR PARISH 13. STATE	
30-045-26276	6709' GL		San Juan	New Mexico
18	Check Appropriate Box To Indicate I	Nature of Notice, Report, or O	other Data	
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	HEPAIRING W	V BLL
FRACTORE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	!
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDON MEN	(T*
REPAIR WELL	CHANGE PLANS	(Other) Spud and	<u>Surface Casing</u>	
- Uther-		Nor: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
7 DES RIDE PROPOSED OR COM- proposed work. If well nent to this work.) *	PLETED OPERATIONS: Clearly state all pertiner is directionally drilled, give subsurface local	and the second of the second o		

MI & RU Four Corners Rig #7. SPUD 12-1/4" hole 4-1-85. Drilled and surveyed ahead to 406'. RU and ran 10 jts 805/8", 24#, K-55, STC casing and set @ 406'. Cemented with 280 sx Class "B" cement + 1/4#/sxcelloseal + 2% CaCl₂ (1.18 cuft/sx - 330.4 cuft). Displaced with 23.5 bbls fresh water. Displace approximately 120 sx cement to pit. Cement to surface. Bumped plug 4-2-85. Float held. NU BOP. Test blind rams, pipe rams and manifold to 250 psi for 5 mins and 3000 psi for 15 minutesheld OK. Test casing to 1000 psi for 30 minutes - OK. Drilled cement. Drilling ahead 4-2-85.

18	I hereby certify that the foregoing is true and correct		
	SIGNED L.B. Morse / kef	TITLE Operations Manager	DATE 4-12-85
	(This space for Federal or State office use)		WCCFAIFD FOR KECOKD
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:		TITLE	APR ES 1995
			PATRICIAN SERVICE ADEA

*See Instructions on Reverse Side