

TIGHT HOLE

Navajo Allotted Com #1E
NE SE Section 24-25N-10W
San Juan County, New Mexico

- ~~CONFIDENTIAL~~
- 4/2/85 406 Day-1 (406') - WOC. (8-5/8" @ 406')
MW: 9.0# Vis: 60 Pv/Yp: NR
MI RU Four Corners #7. SPUD 2245 hrs 4/1/85. Drld 12-1/4" hole to PD. Circ & cond mud. POH. Ran 10 jts 8-5/8", 24#, K-55, STC csg to 406'. Cmtd w/280 sx Cl "B" + add w/full returns & had cmt to surf. Empd plug. WOC. Surveys: 1/2° @ 96' & 188', 1/4° @ 279', 1/2° @ 371'.
- 4/3/85 2250 Day-2 (1844') - Drlg. (8-5/8" @ 406')
MW: 8.7# Vis: 29 Pv/Yp: NR
WOC. Instl 11" 3000 psi csghd & tst weld to 1000 psi. NU BOPs. Tst BOPs to 250 & 3000 psi. Tst csg to 1000 psi. RIH. Drld cmt 361-406'. Drld 7-7/8" hole to PD. Surveys: 1/4° @ 463', 1/2° @ 555', 1/4° @ 647' & 741', 1/2° @ 1053', 1/4° @ 1367', 1/2° @ 1676', 3/4° @ 1989'.
- 4/4/85 3411 Day-3 (1161') - Drlg. (8-5/8" @ 406')
MW: 8.7# Vis: 30 Pv/Yp: 3/1
Drld to 2299'. TFNB. Drld to 2997'. WO in drl strg. POH & LD 1 DC w/cracked box & 1 DC w/wsh'd pin. PU new bit & RIH. Drld 7-7/8" hole to PD. Surveys: 1/2° @ 2272', 3/4° @ 2584', 2869' & 3183'.
- 4/5-8 5921 Day-7 (2510') - Drlg. (8-5/8" @ 406')
MW: 9.3# Vis: 35 Pv/Yp: 3/1
Drld 7-7/8" hole to 4192' w/TFNB @ 3880'. Trip f/WO in drl strg. Drld to 4490'. Trip f/WO (LD 2 DCs w/cracked box & wshd pin). Drld 7-7/8" hole to PD. Surveys: 3/4° @ 3493', 1° @ 3805', 3/4° @ 4120', 1° @ 4466', 4752' & 5064', 3/4° @ 5378' & 5689'.
- 4/9/85 6260 Day-8 (339') - Drlg. (8-5/8" @ 406')
MW: 9.2# Vis: 43 Pv/Yp: 15/6
Drld to 6071'. POH looking f/WO in DP. RIH. Wshd 120' to btm. Drld 7-7/8" hole to PD. Survey: 1° @ 5970'.
- 4/10/85 6544 Day-9 (284') - Drlg. (8-5/8" @ 406')
MW: 9.3# Vis: 60 Pv/Yp: 14/6
Drld to 6383'. POH. PU new B#6. RIH. Wsh 20' to btm. Drld 7-7/8" hole to PD. Survey: 3/4° @ 6343'.
- 4/11/85 6700 Day-10 (156') - Logging. (8-5/8" @ 406')
MW: 9.2# Vis: 63 Pv/Yp: 18/12
Drld 7-7/8" hole to PD. 12 std sht trip. Circ & cond. Strap out of hole - no correction. RU Schl. Rng DIL/GR/FDC/CNL/Cal @ rept time. Survey: 3/4° @ 6683'.