

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. N00-C-14-20-5199	
2. NAME OF OPERATOR Union Oil Company of California		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo	
3. ADDRESS OF OPERATOR P. O. Box 2620 - Casper, WY 82602-2620		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 940' FEL (NE SE)		8. FARM OR LEASE NAME Federal	
14. PERMIT NO. API No. 30-045-26437		9. WELL NO. 1-E *	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6574' GR (Ungraded)		10. FIELD AND POOL, OR WILDCAT Basin Dakota	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 24, T.25N., R.11W.	
		12. COUNTY OR PARISH San Juan	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other)	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		
PULL OR ALTER CASING	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

6138' T.D.
8-5/8" @ 782' w/530 sx cmt.
4-1/2" @ 6135' w/1400 sx cmt

*Formerly Navajo (I24) Well No. 10
Drilled in 1985

Perfs: 5962-6000' - Covered w/casing patch
6022-6030' - Open
6048-6064' - Retainer set above at 6043'

Completion attempts on Federal Well No. 1-E have been unsuccessful; therefore, Union Oil Company of California proposes to plug and abandon this well to comply with State and Federal regulations.

Proposed Plan of Procedure

1. MIRU. N.U. BOP.
2. P.U. tubing and tag ETD.
3. Spot 50 sacks of class "B" cement (Plug No. 1) from 5959-5312'.

(Continued on Attached Sheet)

18. I hereby certify that the foregoing is true and correct

SIGNED Jim Benson

TITLE Drilling Engineer

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Union Oil Company of California
Federal Well No. 1-E
Basin DAKota Field
San Juan County, New Mexico
1-17-86
Page 2

4. P.U. to 5000'. Spot 10 sacks of class "B" cement (Plug No. 2) from 5000-4870' (to cover across Gallup formation).
5. P.U. to 2350'. Spot 10 sacks of class "B" cement (Plug No. 3) from 2350-2221' (to cover Mesaverde).
6. P.U. to 1500'. Spot 10 sacks of class "B" cement (Plug No. 4) from 1500-1370' (to cover Picture Cliffs).
7. P.U. to 850'. Spot 10 sacks of class "B" cement (Plug No. 5) from 850-721'.
8. P.U. to 60'. Spot 5 sacks of class "B" cement (Plug No. 6) from 60' to surface.
9. Cut off 8-5/8" & 4-1/2" casing 3' below ground level, clean up location, and reseed.

Note: Received verbal approval of above procedure from John Keller, BLM-Branch of Fluid Minerals, Farmington, New Mexico, on 1-15-86.

BUREAU OF LAND MANAGEMENT
Drawer 600
Farmington, New Mexico 87499-00600

Attachment to Notice of
Intention to Abandon

Re: Permanent Abandonment

Well: 1E Federal

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."
2. The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
3. Blowout prevention equipment is required.
4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Surface Management Agency for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
5. The following modifications to your plugging program are to be made (when applicable):

Office Hours: 7:30 A.M. to 4:15 P.M.

GENERAL REQUIREMENTS FOR
PERMANENT ABANDONMENT OF WELLS ON FEDERAL LEASES
FARMINGTON DISTRICT

1. Secure prior approval before changing the approved plugging program.
2. Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs.
3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations.
4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 25 sacks or 100 feet in length, whichever is greater.
5. Any cement plug placed when well is not full of fluid, or when well may be taking fluid, will be touched after cement has set to verify proper location.
6. Mud must be placed between plugs. Minimum consistency of plugging mud must be 9.2 lbs/gal. Brine is to be utilized for mixing mud where possible.
7. Within 15 days after plugging work is completed, file Subsequent Report of Abandonment, form 9-331, in quintuplicate with District Supervisor, U.S.G.S., Drawer 600, Farmington, New Mexico 87499-00600. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
8. All permanently abandoned wells are to be marked with a permanent monument, on which has been stenciled or beaded the well name, well number, and well location by quarter-quarter, section, township, and range. The monument is to be of steel pipe, not less than four inches in diameter, cemented permanently in the ground, and extending four feet above general ground level. The top should be closed with a screw cap, welding, or a cement plug.
9. After plugging work is completed:
 - a. Fill all pits, rat hole and cellar.
 - b. Clean well location of all equipment, concrete bases, pipe, junk and trash.
 - c. Cut or remove tie downs.
 - d. If last well on lease, and no additional drilling is contemplated, fill tank battery pits, remove battery equipment, and clean and level battery location.
 - e. Accomplish surface restoration as specified by the surface management agency or land owner.

All above are minimum requirements: The Subsequent Report of Abandonment will not be approved and the period of liability under the bond of record terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.