

Form 3160-5
(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

WELL ☐ GAS WELL ☒ OTHER

NAME OF OPERATOR

M. J. BRANNON

ADDRESS OF OPERATOR

2240A FOREST PARK BLVD., FORT WORTH, TEXAS 76110

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1850' FSL & 1820' FEL SECTION 28, T25N, R9W

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6650' KB

6. LEASE DESIGNATION AND SERIAL NO.

SF-078309

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL 28

9. WELL NO.

1E

10. FIELD AND POOL, OR WILDCAT

BASIN DAKOTA

11. SEC., T., R., M., OR BLM, AND
SURVEY OR AREA

SEC28-T25N-R9W

12. COUNTY OR PARISH 13. STATE

SAN JUAN

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/29/88: Pressure test casing to 4000 PSI-held.
Perfs 6340-6360', 2 SPF, 41 holes. 3-1/8" csg gun.

Fracture well with 66570 gal Cross-link gel, 107,643# 20/40 sand.

Ave rate = 22 BPM, Ave Press = 2800#. ISIP = 3085#. 15 min SIP = 2413#.

Gel additives: F802 surfactant, 2% KCL, YF230 Dowell gel w/WF30.

Trip in hole with tubing 2-3/8" J-55 eue. Clean out to PBTD 6492'
and set packer at 6273' KB.

RECEIVED
BLM MAIL ROOM

NOV 21 PH 1:49

MINING RESOURCE AREA
ARMINGTON, NEW MEXICO

RECEIVED

NOV 21 1988
OIL CON. DIV
DIST. 9

I hereby certify that the foregoing is true and correct

SIGNED

Richard Brannon

TITLE Petroleum Engineer

DATE 11/15/88

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC

*See Instructions on Reverse Side

BY