

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 58890

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Famous Amos

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat PC

11. SEC. T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 31, T25N, R10W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other

2. NAME OF OPERATOR

Hixon Development Company

3. ADDRESS OF OPERATOR

P.O. Box 2810, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 990' FNL, 1750' FWL, Sec. 31, T25N, R10W

At top prod. interval reported below

At total depth

API #30-045-27356

14. PERMIT NO.

DATE ISSUED

15. DATE SPUNDED

6-23-89

16. DATE T.D. REACHED

6-30-89

17. DATE COMPL. (Ready to prod.)

10-31-89

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

6705' GLE

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

1630'

21. PLUG, BACK T.D., MD & TVD

1585'

22. IF MULTIPLE COMPL., HOW MANY*

N/A

23. INTERVALS DRILLED BY

→

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

1493' - 1498'

25. WAS DIRECTIONAL SURVEY MADE

Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN

Induction Log with Gamma Ray & Compensated Density-Neutron Logs

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
7"	20#	126.6'	8-3/4"	See attached Exhibit "A"	
4-1/2"	11.6#	1624'	6-1/4"	See attached Exhibit "A"	

29. LINE RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
				2-3/8"	1464'	

31. PERFORATION RECORD (Interval, size and number)

1493' - 1498' 0.4" 20 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1493' - 1498'	Acidized with 12 bbls 2% KCL & 250 gal 15% HCL. Fraced with 52,000# 20/40 Arizona sand & 55 gal 70 Q foam.

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
N/A		Pumping					Shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
11/1/89	24	1/8"	→		TSTM			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
0	0	→		TSTM		ACCEPTED FOR RECORD		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

MAY 10 1990

35. LIST OF ATTACHMENTS

NMOCD

FARMINGTON RESOURCE AREA

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED

Aldrich L. Kuchera

TITLE

President

DATE

APR 30 1990

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Basin Fruitland	1474'					
Coal						
Pictured Cliffs	1492'					

HIxon DEVELOPMENT COMPANY
FAMOUS AMOS WELL NO. 1
990' FNL, 1750' FWL
SECTION 31, T25N, R10W
SAN JUAN COUNTY, NEW MEXICO
LEASE NO. NM 58890
COMPLETION REPORT
EXHIBIT "A"

CEMENTING RECORD

- Surface Casing - Mixed and pumped 50 sks. (59 cu. ft.)
Class "B" cement containing 2% CaCl_2 and
1/4#/sk. cellophane flakes. Cement
circulated to surface.
- Production Casing - Mixed and pumped 90 sks. (185 cu. ft.)
Class "B" cement containing 2%
Thriftyment and 1/4#/sk. cellophane.
Tailed in with 110 sks. (129.8 cu. ft.)
of Class "B" cement containing 2% CaCl_2 .
Circulated cement to surface.