Form 3160-5 (November 1983) (Formerly 9-331)

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved,
Budget Bureau No. 1004-0135
Expires August 31, 1985
5. LEASE DESIGNATION AND BERIAL NO

BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a difference description of the proposals.).				SF 078063 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
WELL WELL X	OTHER SUA	1ER 90 APR 30 PM 1: 30		Carson Unit		
2. NAME OF OPERATOR	The state of the s			8. FARM OR LEASE NAME		
Hixon Development Company  Address of Operator				9. WELL NO.		
PO Box 2810, Farmington, New Mexico 87499				<b>33</b> -7		
t. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)			10. FI	10. FIELD AND POOL, OR WILDCAT		
At surface			Bas	Basin Fruitland Coal		
1870' FSL, 1800' FWL, Sec. 7, T25N, R11W				11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA		
14. PERMIT NO.	PDMIC NO.			Sec. 7, T25N, R11W 12. COUNTY OR PARISH 13. STATE		
14. PERMIT NO.	!	15. ELEVATIONS (Show whether DF, RT, GR, etc.)		_		
6. CL	6352' GLE				ew Mexico	
	eck Appropriate Box To Indicate	Nature of Notice, Rep				
MOTICE			SUBSEQUENT REI	CORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF		REPAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATME	ENT	ALTERING CASING		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDI	·	ABANDON MENT*		
(Other)	CHANGE PLANS	(Note: Rapo	Orilling Progress (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
Drilled out f 1345'. Ran C 909', Picture 8rd, ST&C cas float on top jts. Casing Mixed and pum and 1/4#/sk. "B" cement co to surface.	from under casing with 6-1 compensated Density-Neutron de Cliffs - 1186'. Ran 31 cing. BakerLoked cement rof 1st jt. Ran centralizate at 1339.12', PBD at 1 cellophane flakes. Tailed the casing 2% CaCl and 1/4% Pressure tested casing to mpletion operations.	/4" bit April 5, on logs. Log top jts. (1343.12') losed guide shoe ers on tops of 1 299.72'. Cement Class "B" cement d in with 80 sks f/sk. cellophane	1990. Dros as followed of 4-1/2" on 1st jt. st, 3rd, 5 ded casing at containing (94.4 cu flakes. Co	illed to TD of ws: Fruitland, 9.5#, J-55, Ran insert th, 7th, and 9 as follows: ag 2% Thriftym. ft.) of Clasement circulat	i - Oth	
	MAY1 OIL CO	4 1990 N. DIV.	MAY 0	FOR RECORD  8 1990 RESOURCE AREA		
SIGNED OF ALDRICH L.	<i>h</i> .	resident	p	Arm April 26,	1990	
(This space for Federal or S	tate office use)					
APPROVED BY	TITLE			ATE		
CONDITIONS OF APPROVA	L. IE ANI:					

## **NMOCD** \*See Instructions on Reverse Side