Form 3160-5 (November 1983) (Formerly 9-331)

14. PERMIT NO.

UNITED STATES SUBMIT IN TRIPLICATE* Other Instructions on reverse side) **UNITED STATES**

rorm approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO

Sec. 9, T25N, R12W

12. COUNTY OR PARISH 13. STATE

BUREAU OF LAND MANAGEMENT	NM 036254-A
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS X OTHER	7. UNIT AGREEMENT NAME
NAME OF OPERATOR	8. FARM OR LEASE NAME
Hixon Development Company	Bisti Coal 9
ADDRESS OF OPERATOR	9. WBLL NO.
PO Box 2810, Farmington, N.M. 87499	1
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*	10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface	Basin Fruitland Coal
1700' FNL, 1250' FEL, Sec. 9, T25N, R12W	11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

API #30-045-27619

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL TEST WATER SHUT-OFF ALTERING CASING MULTIPLE COMPLETE FRACTUBE TREATMENT PRACTURE TREAT SHOOTING OR ACIDIZING ABANDON MENT* SHOOT OR ACIDIZE Drilling Progress REPAIR WELL CHANGE PLANS (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

15. ELEVATIONS (Show whether DF, RT, GR. etc.)

6192' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded surface at 1:00 p.m. on April 16, 1990. Drilled 8-3/4" hole to 127'. Ran 3 jts. (126.30') of 7", 20#, 8rd, J-55, ST&C casing. BakerLoked top of 1st jt. Casing set at 126.80'. Mixed and pumped 60 sks. (70.8 cu. ft.) Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 600 psi for 30 minutes; test ok.

OIL CON. DIV. DIST. 3

ACCEPTED FOR RECORD

APR 27 1990

8. I hereby certify that the foregoing is true and	Correct President	FARMINGTON RESOURCE AREA 1990
(This space for Federal or State office use)	OH TITLE	ратк
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE
	NEGOD	