

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-25444

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bisti Coal 4

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Basin Fruitland Coal

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T25N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Hixon Development Company

3. ADDRESS OF OPERATOR

P.O. Box 2810, Farmington, New Mexico 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1700' FNL, 1700' FEL, Sec. 4, T25N, R12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6156' GLE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)*

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Drilling Progress

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded surface at 10:00 a.m. on March 5, 1990. Drilled an 8-3/4" hole to 128'. Ran 3 jts. (127.4') of 7", 20#, J-55, 8rd, ST&C surface casing. Casing set at 128'. Cemented surface casing as follows: Mixed and pumped 60 sks. (70 cu. ft.) Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface. WOC. Pressure tested casing to 600 psi for 30 minutes. Test OK.

RECEIVED

MAR 29 1990

OIL CON. DIV.
DIST. 3

Accepted For Record

MAR 23 1990

Chief, Branch of
Mineral Resources
Farmington Resource Area

18. I hereby certify that the foregoing is true and correct

SIGNED

Bruce E. Delventhal
Bruce E. Delventhal

TITLE Petroleum Engineer

DATE March 8, 1990

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCD

*See Instructions on Reverse Side