

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Budget Category No. 1004-0133  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 25444
2. NAME OF OPERATOR Hixon Development Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 2810, Farmington, New Mexico 87499		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1700' FNL, 1700' FEL, Section 4, T25N, R12W		8. FARM OR LEASE NAME Bisti Coal 4
14. PERMIT NO.		9. WELL NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6156' GLE		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4, T25N, R12W
		12. COUNTY OR PARISH San Juan
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Progress

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

XX

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled out from under casing with 6-1/4" bit March 6, 1990. Drilled to TD of 1200'. Ran Compensated Density-Neutron log with calliper and Gamma Ray. Log tops as follows: Fruitland Basal Coal - 1063', Pictured Cliffs - 1120'. Ran 28 jts. (1215.32') of 4-1/2", 10.5#, J-55, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of shoe jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1201.28', PBD at 1156.76'. Cemented casing as follows: Mixed and pumped 75 sks. (154.5 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 600 psi for 30 minutes. Test ok. Waiting on completion operations.

RECEIVED

MAR 29 1990

OIL CON. DIV.

DIST. 3

Accepted For Record

MAR 28 1990

18. I hereby certify that the foregoing is true and correct

SIGNED

Aldrich L. Kuchera

(This space for Federal or State office use)

TITLE President

Chief, Branch of  
Mineral Resources  
Farmington Resource Area

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE MAR 19 1990

\*See Instructions on Reverse Side