Ferm 5160--5 (November 1983) (Formerly 9-331)

16.

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

BUREAU OF LAND MANAGEMENT

korm approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

SF 078063 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

·ì						- ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	5.	LEASE	DESI	GNATION	AND	SERIAL	٨

1DV	NOTICEC	ALIN	DEDODIC	ONLA	AMELLO

SUNDRY NOTICES AND REPORTS ON

(1)	Use "APPLICATION FOR PERMIT" for such proposals.)	t reservoir.
i. ort	GAS (T)	7. UNIT AGREEMENT NAME
WELL	GAS WELL XX OTHER	Carson Unit
2. NAME (F OPERATOR	8. FARM OR LEASE NAME
Hixo	n Development Company	A 66
3. ADDRES	OF OPERATOR	9. WELL NO.
PO E	ox 2810, Farmington, N.M. 87499	323-7
	N OF WELL (Report location clearly and in accordance with any State requirements space 17 below.)	ts. • 10. FIELD AND POOL, OR WILDCAT
At suri		Basin Fruitland Coal
1870	' FSL, 1800' FWL, Sec. 7, T25N, R11W	11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA
	API #30-045-	27661 Sec. 7, T25N, R11W
4. PERMIT	NO. 15 ELEVATIONS (Show whether DF, RT, GR. etc.)	12. COUNTY OR PARISH 13. STATE
	6352' GLE	San Juan New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			1	SUBSEQUENT EXPORT OF:		
	L		13	(~·····)	۳	
TEST WATER SHUT-OFF		PULL OR ALTER CASING	1	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTUBE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other)Drilling Progr		X
(Other)				(Note: Report results of multi Completion or Recompletion Rej	ple completion on Well port and Log form.)	

17. DESCRIBE CHOPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded surface at 2:00 p.m. on April 4, 1990. Drilled 8-3/4" hole to 127'. Ran 3 jts. (125.8') of 7", 20#, J-55, 8rd, ST&C casing. Casing set at 127.10'. Cemented casing as follows: Mixed and pumped 60 sks. (70 cu. ft.) Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface. WOC. Pressure tested casing to 600 psi for 30 minutes; held OK.



OIL CON. DIV. DIST. 3

ACCEPTED FOR RECORD

APR 23 1990

FARMINGTON RESOURCE AREA RY 22/

8. I hereby certify that the foresoing is true and corre	Anne President	APR 1 7 1990
Aldrich L. Kuchera Mok (This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE

*See Instructions on Reverse Side

HOOKA FOR CRIMEDOA

· 自己 (新元)

I want to see the second of th