UNITED STATES (June 1990) (June 1990) (DEPARTMENT OF THE INTERIOR		FORM APPROVED Budget Burcau No. 1004-0135 Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT		5. Lease Designation and Serial No. NM 25449
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well Well Other		8. Well Name and No.
2. Name of Operator Giant Exploration & Production Company		Bisti Coal 22 #1 9. API Well No.
3. Address and Telephone No.		30-045-27673
P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area Basin Fruitland Coal
		11. County or Parish, State
2510' FNL, 1850' FEL, Sec. 22, T25N, R12W		San Juan, New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
KZZY	Recompletion	New Construction
Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Drilling Progress	Dispose Water (Note: Report results of multiple completion on Well
	pertinent details, and give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Log form.)
Drilled out from under casing with 6-1/4" bit September 10, 1990. Drilled to TD of 1251'. Ran Compensated Density-Neutron Logs with Garma Ray. Log tops as follows: Fruitland - 1074', Basal Fruitland Coal - 1130', Pictured Cliffs - 1168'. Ran 30 jts. (1260.20') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1250.99', PBD at 1215.01'. Cemented casing as follows: Mixed and pumped 75 sks. (154.5 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cenent circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.		
14. I hereby certify that the foregoing is true and correct Signed	President President	OCT 9 1990 ·
(This space for rederal or state office use) La Mon		ED FOR RECORD
Approved by	Fred State S	CT 23 1990
Title 18 U.S.C. Section 1001, makes it a crime for any person or representations as to any matter within its jurisdiction.	knowingly and willfully to make to any department or age icy of the United	GTON RESOURCE AREA States any false, fictitious or fraudulent statements