Fon (1) 0.5 UNI June (10) OCT 2 DEPÁRTMEN BUREAU OF		
UNITED STATES June 1999 DEPARTMENT OF THE INTERIOR		FORM APPROVED Budget Burcau No. 1004-0135 Expires: March 31, 1993
BUREAU OF LAND MANAGEMENT ON ONDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		5. Lease Designation and Serial No. 14-20-603-1423 6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE		Navajo Indian Allotted 7. If Unit or CA, Agreement Designation
i. Type of Well Oil Gas Well KX Well Other		8. Well Name and No.
2. Name of Operator Giant Exploration & Production Company		Bisti Coal 3 Com #1 9. API Well No.
3. Address and Telephone No. PO Box 2810, Farmington, N.M. 87499 (505) 326-3325		30-045-28008 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D., 790' FSL, 790' FWL, Sec. 3, T.		Basin Fruitland Coal II. County or Parish, State
2. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPO	San Juan, New Mexico RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
XX Subsequent Report	Recompletion Plugging Back	New Construction Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Casing Repair Altering Casing SOther Drilling Progress	Conversion to Injection Dispose Water

IIII T

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any projosed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

(Note: Report results of multiple completion on Well Com-letion or Recompletion Report and Log form.)

Drilled out from under casing with 6-1/4" bit September 14, 1990. Drilled to TD of 1250'. Ran Compensated Density-Neutron logs with calliper and gamma ray. Log tops as follows: Fruitland - 1000', Basal Fruitland Coal - 1084', Pictured Cliffs - 1134'. Ran 30 jts. (1254.02') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1250.08', PBD at 1214.83'. Cemented casing as follows: Mixed and pumped 70 sks. (144.2 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 70 sks. (82.6 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

14. I hereby certify that the foregoing is true and correct	: President	ACCEPTED FOR RECORDU
(This space for Federal of State office Use) a mon		OCT 1 9 1990
Approved by Title Conditions of approval, if any:	NMOCD	FARMINGTON RESOURCE AREA BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.