Form 3160-5 (June 1990)

Final Abandonment

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

	Expires:	March	31, 19	93
Lease	Designat	ion and	Serial	No

6. If Indian, Allottee or Tribe Name

Water Shut-Off

Conversion to Injection
Dispose Water

(Note: Report results of multiple completion on Well

5.

NM 25446

SUNDRY	NOTICES	AND	REPORTS	ON WELLS	;
SUINDINI	HOLICES	$\Delta \Pi \nabla$	HEI OHIO	O14 44 FFF	,

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT	7. If Unit or CA, Agreement Designation		
1. Type of Well Oil Well X Well Other 2. Name of Operator Giant Exploration & Production Company 3. Address and Telephone No. PO Box 2810, Farmington, N.M. 87499 (505) 326-3325 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1600' FSL, 790' FWL, Sec. 18, T25N, R12W		8. Well Name and No. Bisti Coal 18 #2 9. API Well No. 30-045-28141 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 11. County or Parish, State	
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE,	San Juan, New Mexico REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF A	ACTION	
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction	

Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Casing Repair

Altering Casing

Drilled out from under casing with 6-1/4" bit September 4, 1990. Drilled to TD of 1500'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 1160', Basal Fruitland Coal - 1340', Pictured Cliffs - 1392'. Ran 36 jts. (1503.30') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. BakerLoked the pin of 2nd jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1499.19', PBD at 1464.54'. Cemented casing as follows: Mixed and pumped 80 sks. (164.8 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 85 sks. (100.3 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

4. I bereby certify that the foregoing is true and correct Signed	President	Date SEP 1 7 1990
(This space for Federal or State office use)	Title	ACCEPTED FOR RECORD
Approved by		SEP 2 0 1990

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any waster facilities or fraudulent statements or representations as to any matter within its jurisdiction.