Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM 39017 SUNDRY NOTICES AND REPORTS ON WELLS: 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well 8. Well Name and No. 2. Name of Operator Devon Nielsen #1 9. API Well No. Giant Exploration & Production Company 3. Address and Telephone No. 30-045-28195 10. Field and Pool, or Exploratory Area P.O. Box 2810, Farmington, N.M. 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Bisti Lower Gallup 11. County or Parish, State 330' FNL, 330' FEL, Sec. 5, T24N, R11W San Juan, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment New Construction Recompletion Subsequent Report Non-Routine Fracturing Plugging Back Water Shut-Off Casing Repair Conversion to Injection Final Abandonment Notice Altering Casing Other Drilling Progress Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spudded surface at 2:00 P.M. on September 27, 1990. Drilled 12-1/4" hole to 370' KB. Ran 8 jts. (348.98') of 8-5/8", 24#, J-55, 8rd, ST&C casing. BakerLoked guide shoe on bottom of 1st jt. Ran centralizers on the tops of 1st, 3rd, 5th and 7th jts. Casing set at 363.91'. Mixed and pumped 230 sks. (271.4 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 600 psi for 30 minutes; test ok.

recrtify that the foregoing is true and correct 8 1990 OCT President Date (This space for Federal or State office they a Approved by _______ Conditions of approval, if any: ∙0C†™22-1990 **FARMINGTON RESOURCE AREA**