Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004~0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

San Juan, New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS	11111:2	SF-078056
SUMPRI MOTICES MAD REPORTS ON WELLS	 4. 11. 15	6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals	1. 20
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
. Type of Well Oil Gas Well Other	8. Well Name and No.
Name of Operator	Bisti Coal 7 #2
Giant Exploration & Production Company	9. API Well No.
. Address and Telephone No.	30-045-28386
P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal
17/5' PMI 10/5' PFI Soc 7 T25M P12M	11. County or Parish, State

2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION A CONTROL OF THE	TYPE OF ACTION	
Notice of Intended Subsequent Report JAN1 8 1991 Final Abandonme Mcc CON. DIST. 3	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Stock Other Drilling Progress	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit November 17, 1990. Drilled to TD of 1310'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 979', Basal Fruitland Coal - 1133', Pictured Cliffs - 1176'. Ran 31 jts. (1306.99') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1303.99', PBD at 1264.51'. Cemented casing as follows: Mixed and pumped 75 sks. (154 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane. Tailed in with 70 sks. (82.6 cu. ft.) of Class "B" cement containing 2% CaCl₂ and 1/4#/sk. cellophane. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

Signo All Presiden	t ACCEPTED FOR RECORD
Aldrich L. Kuchera how (This space for Federal or State office use) Approved by Title Conditions of approval, if any:	JAN _D 10 1991
	FARMINGTON RESOURCE AREA